

## Adaptador reductor esmerilado, WITEG®

Ref.: WITEG0.500 | Categoría: Conectores y adaptadores

### Descripción

---



Reduction adapter, cone

- Made of borosilicate glass 3.3
- Acc. DIN 12257



## Especificaciones técnicas

Referencia	Producto	Esmerilado macho (Inferior)	Esmerilado hembra (Superior)	Cumple DIN 12257	Env
0 500 000	Reduction adapter, cone ST 14/23, socket ST 10/19	14/23	10/19	-	1
0 500 001	Reduction adapter, cone ST 19/26, socket ST 14/23	19/26	14/23	Sí	1
0 500 002	Reduction adapter, cone ST 24/29, socket ST 14/23	24/29	14/23	-	1
0 500 003	Reduction adapter, cone ST 29/32, socket ST 14/23	29/32	14/23	Sí	1
0 500 004	reduction adapter, cone ST 24/29, socket ST 19/26	24/29	19/26	-	1
0 500 005	Reduction adapter, cone ST 29/32, socket ST 19/26	29/32	19/26	Sí	1
0 500 006	Reduction adapter, cone ST 29/32, socket ST 24/29	29/32	24/29	-	1
0 500 007	Reduction adapter, cone ST 45/40, socket ST 24/29	45/40	24/29	-	1
0 500 008	Reduction adapter, cone ST 45/40, socket ST 29/32	45/40	29/32	Sí	1
0 500 009	Reduction adapter, cone ST 60/46, socket ST 45/40	60/46	45/40	-	1
0 500 010	Reduction adapter, cone ST 71/51, socket ST 45/40	71/51	45/40	-	1
0 500 011	Reduction adapter, cone ST 71/51, socket ST 60/46	71/51	60/46	-	1
0 500 012	Reduction adapter, cone ST 60/46, socket ST 29/32	60/46	29/32	-	1

Referencia	Producto	Esmerilado macho (Inferior)	Esmerilado hembra (Superior)	Cumple DIN 12257	Env
0 500 013	Reduction adapter, cone ST 34/35, socket ST 19/26	34/35	19/26	-	1
0 500 014	Reduction adapter, cone ST 34/35, socket ST 24/29	34/35	24/29	-	1
0 500 015	Reduction adapter, cone ST 34/35, socket ST 29/32	34/35	29/32	-	1
0 500 016	Reduction adapter, cone ST. 50/42, socket 29/32	50/42	29/32	-	1
0 500 017	Reduction adapter, cone ST 55/44, socket 29/32	55/44	29/32	-	1
0 500 018	Reduction adapter, cone 14/23, socket ST 12/21, acc. to DIN 12257	14/23	12/21	Sí	1
0 500 019	Reduction adapter, cone ST 40/38, socket ST 19/26, acc. to DIN 12257	40/38	19/26	Sí	1
0 500 020	Reduction adapter, cone 45/40, socket ST 34/35, acc. to DIN 12257	45/40	34/35	Sí	1