Pontraga Suministros de Laboratorio
www.pontraga.es
info@pontraga.es

Bomba de vacío Rocker 300 -680mmHg (106mbar) 20l/min

Ref.: ROCKER.00829 167300-22 | Categoría: Bombas de vacío y presión



Descripción

Ideal para:

- filtración para pruebas de microbiología
- muestreo de aire
- prueba de sólidos suspendidos
- filtración al vacío

Características:

- Pistón sin lubricante ni aceite.
- Sin contaminación del aire
- Libre de mantenimiento
- El filtro ProteTM evita que el líquido sea aspirado por la bomba y filtra las partículas y la humedad.
- Certificado CE, CSA y RoHs, protección IP 30.

Controlador:

- El dispositivo de protección térmica garantiza el apagado de la bomba cuando se sobrecalienta y reanuda su funcionamiento cuando la temperatura baja.

Bomba de vacío Rocker 300, trampa de humedad/regulador de vacío, protección contra desbordamiento, cable de alimentación, manual de instrucciones

Especificaciones técnicas

Referencia	Modelo
00829 167300-22	Rocker 300 oil-free vacuum pump, lubricant and oil free piston, maintenance-free, ProteTM filter, thermal protection device, CE certified, AC 230 V, max. vacuum -680 mmHg, flow rate 20 l/min, motor ratio 1450 rpm, 1/8 HP, port thread 5/16 inch (8 mm), moisture trap, overflow protection, 26.8 x 13.5 x 20.4 cm, 4.1 kg, *new model* **Rango de vacío:** -680 mmHg (106 mbar) **Caudal:** 20 l/min **Speed (rpm):** 1450 rpm **Conector tubo:** 5/16 inch (8 mm) **Nivel de ruido:** 50 dB **Dim. (WxLxH):** 13.5x26.8x20.4 cm Show moreShow less