Pontraga Suministros de Laboratorio
www.pontraga.es
info@pontraga.es

Bomba de vacío Rocker 300 DC -650mmHg (146mbar) 25l/min

Ref.: ROCKER.00829 167330-00 | Categoría: Bombas de vacío y presión

Descripción



Ideal para:

- filtración para pruebas de microbiología
- muestreo de aire
- prueba de sólidos suspendidos
- filtración al vacío

Características:

- Pistón sin lubricante ni aceite.
- sin contaminación del aire
- libre de mantenimiento
- El filtro ProteTM evita que el líquido sea aspirado por la bomba y filtra las partículas y la humedad.
- Certificado CE y CSA

Controlador:

- El dispositivo de protección térmica garantiza el apagado de la bomba cuando se sobrecalienta y reanuda su funcionamiento cuando la temperatura baja.

Bomba de vacío Rocker 300 DC, trampa de humedad/regulador de vacío, protección contra desbordamiento, cable de alimentación, manual de instrucciones

Especificaciones técnicas

Referencia	Modelo
00829 167330-00	Rocker 300 DC oil-free vacuum pump, lubricant and oil free piston, maintenance-free, ProteTM filter, thermal protection device, CE certified, DC 12 V, max. vacuum -650 mmHg , flow rate 25 l/min, motor ratio 1800 rpm, 1/8 HP, port thread 5/16 inch (8 mm), moisture trap, overflow protection, 27.2 x 12.1 x 16.5 cm, 3.5 kg **Rango de vacío:** -650 mmHg (146 mbar) **Caudal:** 25 l/min **Speed (rpm):** 1800 rpm **Conector tubo:** 5/16 inch (8 mm) **Nivel de ruido:** 50 dB **Dim. (WxLxH):** 13.5x26.8x20.4 cm Show moreShow less