Termómetro digital ultrapreciso para sondas PT1000 4 hilos Sensotec PRO 11x



Ref.: SENSECA.PRO111 | Categoría: Termómetros digitales

Descripción

SENSECA PRO 111 y PRO 115 son medidores portátiles profesionales de alta gama para sondas Pt100 de 4 hilos con un amplio conjunto de funciones, robustez de alta calidad y comodidad de operación para un uso seguro y confiable. PRO 115 también tiene capacidad de registro de datos.

Especificaciones técnicas

Referencia	Modelo	Set-Option	Rango	Resolución	An×F×Al	Sonda	Env
486651	PRO115 With data logger, Up to 1 million data sets, file system based Incl batteries, Quickstart, USB-C cable	Device in carton box, test protocol, without temperature probe	-200.0... 850.0 °C	0,01 °C	78×38×170 mm	Without temperature probe	1
487735	PRO111-DAKKS1 Standard Incl batteries, Quickstart	incl. AX111-D3-AA-150, adjustment CvD, DAKKS calibration -20, 0, 70 °C Case PRO-400	-200.0... 850.0 °C	0,01 °C	78×38×170 mm	AX111-D3-AA-150	1
487737	PRO111-ISO3 Standard Incl batteries, Quickstart	incl. AX111-D3-AA-150, ISO calibration -20, 0, 70 °C, Case PRO-400, not DAkkS/ACCREDIA accredited	-200.0... 850.0 °C	0,01 °C	78×38×170 mm	AX111-D3-AA-150	1
487736	PRO111-ISO3A Standard Incl batteries, Quickstart	incl. AX111-D3-AA-150, ISO calibration 0, 100, 250 °C, Case PRO-400, not DAkkS/ACCREDIA accredited	-200.0... 850.0 °C	0,01 °C	78×38×170 mm	AX111-D3-AA-150	1
487734	PRO115-DAKKS1 With data logger Up to 1 million data sets, file system based Incl batteries, Quickstart, USB-C cable	incl. AX111-D3-AA-150, adjustment CvD, DAKKS calibration -20, 0, 70 °C Case PRO-400	-200.0... 850.0 °C	0,01 °C	78×38×170 mm	AX111-D3-AA-150	1
487738	PRO115-ISO3 With data logger Up to 1 million data sets, file system based Incl batteries, Quickstart, USB-C cable	incl. AX111-D3-AA-150, ISO calibration -20, 0, 70 °C, Case PRO-400, not DAkkS/ACCREDIA accredited	-200.0... 850.0 °C	0,01 °C	78×38×170 mm	AX111-D3-AA-150	1

Referencia	Modelo	Set-Option	Rango	Resolución	An×F×Al	Sonda	Env
487414	PRO115-ISO3A With data logger Up to 1 million data sets, file system based Incl batteries, Quickstart, USB-C cabl	incl. AX111-D3-AA-150, ISO calibration 0, 100, 250 °C, Case PRO-400, not DAkkS/ACCREDIA accredited	-200.0... 850.0 °C	0,01 °C	78×38×170 mm	AX111-D3-AA-150	1
486650	PRO111 Standard Incl batteries, Quickstart	Device in carton box, test protocol, without temperature probe	-200.0... 850.0 °C	0,01 °C	78×38×170 mm	Without temperature probe	1